



Technical description

Electronic machine with micro-processor aided controls, with LCD display and touch screens.

- Body in AISI 304 – 18/8 polished stainless steel – with tenorite grey finishing
- Always-on touch screen panels with LED
- Touch screen controlling:
 - programmable on/off cycles;
 - digital clock;
 - volume settings check;
 - display-assisted volume set-up;
 - water level check;
 - language selection.
- Resettable coffee and hot water counter
- Periodical maintenance program
- Softener regeneration program
- Boiler level check with alarms against lack of water
- Inbuilt volumetric pump with balanced by-pass
- Electronic cup warmer
- Heating element engaging when the boiler is full, with safety thermostat
- Programmable hot water dispenser
- Two steam wands in stainless steel
- Electronic boiler temperature control (Thermo-PID)
- Ergonomic filter holders
- Hot water mixer
- Power saving mode when the machine is in stand-by
- High Group version – up to 185 mm tall cups

Optional accessories upon request:

- Pre-infusion valve on the brewing group
- Milk warmer/frother – temperature-controlled steam wand “EPS” controlled through the display
- 4-temperature hot water mixer E4T
- Easy-to-fit pods and capsules kit for the brewing groups
- Cappuccinatore or milk frother

Model	F 2006 Life	F 2006 Life
Version	2 GROUPS	3 GROUPS
Dimensions mm.	770x560x580h	1010x560x580h
Bolier capacity	11 lt.	17 lt.
Power	4500 watt	5400 watt
Voltage	220/240V single phase, 380/415V threephase, 110V single phase (2.400W)	220/240V single phase, 380/415V threephase
Weight	87 kg	98 kg